

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08

Page 1 / 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

SWAG 15 93 2936 Engine Oil 5W - 40

Article number: 15 93 2936, 15 93 2937, 15 93 2938, 15 93 2939, 15 93

2940

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

1.3 Details of the supplier of the safety data sheet

Company SWAG Autoteile GmbH

Am Kiesberg 4-6

42117 Wuppertal / GERMANY Phone +49 (0)202 26454-0 Fax +49 (0)202 26454-5000 Homepage www.swag.de E-mail info@swag.de

Address enquiries to

Technical information info@swag.de Safety Data Sheet info@swag.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Eye Irrit. 2: H319 Causes serious eye irritation.

Skin Sens. 1: H317 May cause an allergic skin reaction.

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms



Signal word WARNING

Contains: Calcium long chain alkyl aryl sulfonate

Hazard statements H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice / attention.

P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of

disposal.



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08 Page 2 / 11

2.3 Other hazards

Human health dangers Frequent persistent contact with the skin can cause skin irritation.

If swallowed or in the event of vomiting, risk of product entering the lungs.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards none

SECTION 3: Composition / Information on ingredients

Product-type:

3.2 The product is a mixture.

| Range [%] | Substance |
|-----------|---|
| 30 - < 60 | Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based |
| | CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5, Reg-No.: 01-2119474889-13-XXXX |
| | GHS/CLP: Asp. Tox. 1: H304 |
| 1 - < 5 | Polyolefine polyamine succinimide, polyol |
| | CAS: 147880-09-9, EINECS/ELINCS: Polymer |
| | GHS/CLP: Aquatic Chronic 4: H413 |
| 1 - < 2,5 | Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased |
| | CAS: 68784-26-9 |
| | GHS/CLP: Aquatic Chronic 4: H413, |
| | M_acute = 1 |
| 1 - < 2,5 | Bis(nonylphenyl)amine |
| | CAS: 36878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 05-2114603735-5 |
| | GHS/CLP: Aquatic Chronic 4: H413 |
| 1 - < 2,5 | Calcium long chain alkyl aryl sulfonate |
| | CAS: 722503-68-6, EINECS/ELINCS: 682-816-2 |
| | GHS/CLP: Skin Sens. 1: H317 - Aquatic Chronic 4: H413 |
| 1 - < 2,5 | Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts |
| | CAS: 68784-31-6, EINECS/ELINCS: 272-238-5, Reg-No.: 01-2119657973-23-XXXX |
| | GHS/CLP: Eye Dam. 1: H318 - Aquatic Chronic 2: H411 |
| < 0,25 | Phenol, dodecyl-, branched |
| | CAS: 121158-58-5, EINECS/ELINCS: 310-154-3, EU-INDEX: 604-092-00-9 |
| | GHS/CLP: Skin Corr. 1C: H314 - Aquatic Chronic 1: H410 - Repr. 1B: H360F - Aquatic Acute 1: H400 - Eye Dam. |
| | 1: H318, |
| | M_acute = 10 |

Comment on component parts

All chemical substances in this material are included on or exempted from listing on the

IECSC Inventory.

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Consult a doctor immediately.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

SWAG[®]

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08

Page 3 / 11

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media for

foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.

Risk of formation of toxic pyrolysis products.

Phosphorus oxides (POx). Sulphur oxides (SOx). Nitrogen oxides (NOx).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.

Do not smoke.

Fire class (DIN EN 2): B

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets.



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08 Page 4 / 11

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container. Prevent penetration into the ground.

Do not store together with oxidizing agents.

Keep container tightly closed. Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

not applicable

DNEL

| Substance | | |
|---|--|--|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1 | | |
| Industrial, inhalative, Long-term - local effects: 5.6 mg/m³ 5.6 mg/m³. | | |
| Industrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day 5.6 mg/m³. | | |
| Industrial, inhalative, Long-term - systemic effects: 2.7 mg/m³. | | |
| general population, oral, Long-term - systemic effects: 0.74 mg/kg bw/day 5.6 mg/m³. | | |
| Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts, CAS: 68784-31-6 | | |
| Industrial, dermal, Acute - systemic effects: 100 mg/kg bw/d. | | |
| Industrial, dermal, Long-term - systemic effects: 10,42 mg/kg bw/d. | | |
| Industrial, inhalative, Acute - systemic effects: 496,4 mg/m³. | | |
| Industrial, inhalative, Long-term - systemic effects: 2,93 mg/m³. | | |
| general population, oral, Acute - systemic effects: 29 mg/kg bw/d. | | |
| general population, oral, Long-term - systemic effects: 0,21 mg/kg bw/d. | | |
| general population, dermal, Acute - systemic effects: 50 mg/kg bw/d. | | |
| general population, dermal, Long-term - systemic effects: 2,1 mg/kg bw/d. | | |
| general population, inhalative, Acute - systemic effects: 198,6 mg/m³. | | |
| general population, inhalative, Acute - systemic effects: 11,75 mg/m³. | | |
| | | |

PNEC

| Substance | |
|---|--|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1 | |
| oral (food), 9,33 mg/kg. | |
| Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts, CAS: 68784-31-6 | |
| oral (food), 8,33 mg/kg. | |
| soil, 0,0548 mg/kg. | |
| sewage treatment plants (STP), 3,8 mg/l. | |
| sediment (freshwater), 0,0701 mg/l. | |
| sediment (seawater), 0,00701 mg/l. | |
| freshwater, 0,0040 mg/l. | |
| seawater, 0,0046 mg/l. | |

SWAG[®]

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08

Page 5 / 11

8.2 Exposure controls

Additional advice on system design

Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

General exposure limit for oil mist should be noted.

Eye protection If there is a risk of splashing:

safety glasses

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0,11 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).

Skin protection light protective clothing

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Respiratory protection Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards none

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form liquid

Coloryellow-brownOdorcharacteristicOdour thresholdnot applicablepH-valuenot applicablepH-value [1%]not applicable

Boiling point [°C]No information available.

Flash point [°C] > 200 (ISO 2592)

Flammability (solid, gas) [°C] No information available.

Lower explosion limit No information available.

Upper explosion limit No information available.

Oxidising properties no

Vapour pressure/gas pressure [kPa] < 0,01 (20°C)

Density [g/ml] 0,858 (DIN 51757) (15 °C / 59,0 °F)

Bulk density [kg/m³] not applicable
Solubility in water immiscible

Partition coefficient [n-octanol/water] No information available.

Viscosity > 20,5 mm²/s (40° C)

ca. 13,5 - 15 mm²/s (100°C) (DIN 51562/T1)

Relative vapour density determined

in air

No information available.

Evaporation speed No information available.

Melting point [°C] ca. -36(ISO 3016)

Autoignition temperature [°C] No information available.

Decomposition temperature [°C] No information available.

9.2 Other information

none



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08 Page 6 / 11

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

In the case of heating following (decomposition) products may occure: Hydrogen sulfide (H2S).



Page 7 / 11

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product

oral, Based on the available information, the classification criteria are not fulfilled .:

inhalative, Based on the available information, the classification criteria are not fulfilled.:

dermal, Based on the available information, the classification criteria are not fulfilled .:

Substance

Bis(nonylphenyl)amine, CAS: 36878-20-3

LD50, oral, Rat: >5000 mg/kg (IUCLID).

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

LD50, dermal, Rabbit: >= 2000 mg/kg (OECD 402).

LD50, oral, Rat: >= 5000 mg/kg (OECD 401)

LC50, inhalative, Rat: >= 5,53 mg/l (OECD 403).

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts, CAS: 68784-31-6

Based on the available information, the classification criteria are not fulfilled.

Based on the available information, the classification criteria are not fulfilled.

LD50, dermal, Rabbit: >5000 mg/kg bw.

LD50, oral, Rat: 2750 mg/kg bw.

Serious eye damage/irritation Toxicological data of complete product are not available.

Irritant

Calculation method

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Calculation method

Specific target organ toxicity —

single exposure

Specific target organ toxicity —

repeated exposure

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Reproduction toxicity No classification. Calculation method

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08

Page 8 / 11

SECTION 12: Ecological information

12.1 Toxicity

Product

Based on the available information, the classification criteria are not fulfilled .:

Substance

Bis(nonylphenyl)amine, CAS: 36878-20-3

LC50, (96h), Crustacea: 18,9 - 39,2 mg/l.

LC50, (96h), fish: >1000 mg/l.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

EL50, (24h), Daphnia magna: >10000 mg/l (OECD).

LL50, (96h), Pimephales promelas: >100 mg/l (OECD).

NOEL, (21d), Daphnia magna: 10 mg/l (OECD).

NOEL, (72h), Pseudokirchneriella subcapitata: >100 mg/l (OECD)

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts, CAS: 68784-31-6

EC50, (16h), Pseudomonas putida: 380 mg/l.

IC50, (21d), Daphnia magna: >0,8 mg/l.

EL50, (48h), Daphnia magna: 75 mg/l.

EL50, (72h), Desmodesmus subspicatus: 410 mg/l.

NOEC, (21d), Daphnia magna: 0,8 mg/l.

NOELR, (48h), Daphnia magna: 32 mg/l.

NOELR, (96h), Oncorhynchus mykiss: 3,2 mg/l.

LL50, (96h), Oncorhynchus mykiss: 4,4 mg/l.

EC0, (16h), Pseudomonas putida: 200 mg/l.

LOEC, (21d), Daphnia magna: 0,8 mg/l.

12.2 Persistence and degradability

Behaviour in environment

compartments

not determined

Behaviour in sewage plant

Can be separated out mechanically in purification plants.

Biological degradability

The product is only slightly biodegradable.

Slightly eliminable from water.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment.



SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08

Page 9 / 11

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material c It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!

Coordinate disposal with the disposal contractor/authorities if necessary.

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended) 130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

150110* Waste no. (recommended)

SECTION 14: Transport information

14.1 UN number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

IMDG

not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

IMDG

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with not applicable

IMDG

Air transport in accordance with IATA not applicable

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08

Page 10 / 11

14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

IMDG

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to

ADR/RID

no

Inland navigation (ADN)

no

Marine transport in accordance with no

IMDG

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008;

75/324/EEC (2016/2037/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS ADR (2019); IMDG-Code (2019, 39. Amdt.); IATA-DGR (2019)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.

- VOC (2010/75/CE)

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 03)

H411 Toxic to aquatic life with long lasting effects.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H314 Causes severe skin burns and eye damage.

H360F May damage fertility.

H410 Very toxic to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 30.10.2019, Revision 30.10.2019

Version 09. Supersedes version: 08

Page 11 / 11

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level DNEL = Derived No Effect Level EC50 = Median effective concentration ECB = European Chemicals Bureau

EEC = European Economic Community EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods IUCLID = International Uniform ChemicaL Information Database

LC50 = Lethal concentration, 50% LD50 = Median lethal dose LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value - time-weighted average TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)

Skin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method)

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position